



Dahua Security Camera 06 Pack, Free Installation With Accessory Kit

Model No: DH-6-CAMERA-PACK



Price:

Rs. 233,999

Warranty:

2 Years(s) manufacturer warranty.
2 Year Manufacturer Warranty.

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- Type: CCTV Kits
- Model: DH-XVR1B08 Digital Video Recorder, ST2000VX003 Hard Disk, HAC-B1A21P BULLET CAMERA x 6
- System:Main Processor: Embedded processor
- System:Operating System: Embedded LINUX
- Video:Input: 8 channels, BNC
- Video:Standard: PAL/NTSC
- Display:Interface: 1 HDMI, 1 VGA
- Display:Resolution: 1920 × 1080, 1280 × 1024, 1280 × 720
- Display:Display Split: When IP extension mode not enabled: 1/4/8/9
- Display:Privacy Masking: 4 rectangular zones (each camera)
- Display:OSD: Camera title; Time; Video loss; Camera lock; Motion detection; Recording
- Recording:Video/Audio Compression: AI Coding/H.265+/H.265/H.264+/H.264
- Recording:Record Rate: 8-channel: the 1st channel 1080N/720p(1 fps–25/30 fps), others 1080N/720p(1 fps–15 fps); 960H/D1/CIF/(1 fps–25/30 fps)
- Recording:Bit Rate: 32 kbps–4096 kbps per channel
- Recording:Record Mode: Manual; Schedule (General, Continuous); MD (Video detection: Motion Detection, Video Loss, Tampering); Alarm; Stop
- Recording:Record Interval: 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
- Video Detection:Trigger Events: 1 min– 60 min (default: 60 min), Pre-record: 1 s–30 s, Post-record: 10 s–300 s
- Video Detection:Video Detection: Motion Detection, MD Zones: 396(22Å— 18), Video Loss & Camera Blank
- Playback & Backup:Sync Playback: 4/1/2009
- Playback & Backup:Search Mode: Time/Date; Alarm; MD and Exact Search (accurate to second)
- Playback & Backup:Playback Functions: Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection,Digital zoom
- Playback & Backup:Backup Mode: USB Device/Network
- Network:Ethernet: RJ-45 port (10/100M)
- Network:Network Functions: HTTP; HTTPS; TCP/IP; IPv4/IPv6; Wi-Fi; 3G/4G; SNMP; UPnP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; PPPoE; DDNS; FTP; Alarm Server; P2P; IP Search (Supports Dahua IP
- Network:Max. User Access: 128 users
- Network:Smart Phone: iPhone, iPad, Android, Windows Phone
- Storage: SATA 2 TB, 180MB/s, 600000, 8760, 1,000,000hr
- Auxiliary Interface:USB Interface: USB Interface - 2 ports (1 Rear), USB2.0, 22, 300000, 8760, 180,
- Power Supply: DC12V/2A
- Power Consumption: < 7 W (Without HDD)
- Working Environment: -10Â°C ~+55Â°C / 10%~90%RH / 86~106kpa
- Camera:Image Sensor: 1/2.7" 2Megapixel CMOS

- Camera:Effective Pixels: 1920(H)×1080(V), 2MP
- Camera:Electronic Shutter: PAL: 1/25~1/100000s
- Camera:Video Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P
- Camera:Synchronization: Internal
- Camera:Mini. Illumination: 0.04Lux/F1.85, 30IRE, 0Lux IR on
- Camera:Video Output: 1-channel BNC high definition video output/ CVBS standard definition video output (Can switch)
- Camera:Max. IR LEDs Length: Up to 20m (66feet)
- Camera:Day/Night: Auto(ICR) / Color / B/W
- Camera:Backlight Compensation: -
- Camera:Noise Reduction: -
- Camera:Angle of View: H: 93° (103°, 54.7°)
- Camera:Mount Type: Board-in
- Camera:Power Supply: 12V DC ±30%
- Camera:Power Consumption: Max. 2.7W (12V DC, IR on)
- Camera:Working Environment: '-40°C ~ +60°C (-40°F ~ +140°F) / Less than 95% RH
- Camera:Protection: IP67
- Other Information: DH-XVR1B08 Digital Video Recorder, ST2000VX003 Hard Disk, HAC-B1A21P BULLET CAMERA x 6, Free Installation With Accessory Kit
- Dimension: 70mm×70mm×149mm (2.76"×2.76"×5.87")

Date: 2026-04-16 04:47